

DC BIAS CONTROL CIRCUIT, OPTICAL RECEIVER, AND  
DC BIAS CONTROL METHOD

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to a DC bias control circuit for, an optical receiver for, and a DC bias control method of reducing the amount of jitter in regenerated data.

Description of the Prior Art

10 Fig. 12 is a block diagram showing the structure of a prior art optical receiver disclosed in Japanese patent application publication (TOKKAIHEI) No. 11-284572. In the figure, reference numeral 1 denotes a light receiving element for converting an incoming optical signal into an electrical current signal, reference numeral 2 denotes a preamplifier for converting the electrical current signal which flows through the light receiving element 1 into a voltage signal, reference numeral 3 denotes a capacitor for blocking a DC component of the voltage signal from the preamplifier 2 and for allowing an AC component of the voltage signal to pass therethrough, and reference numeral 4 denotes a data regeneration and clock recovery circuit for reshaping and regenerating data from the AC component of the voltage signal which passes through the capacitor 3, and for recovering a clock from the AC component of the voltage signal.

25 In operation, the light receiving element 1 converts an incoming optical signal into an electrical current signal, and the preamplifier 2 then converts the electrical current signal which flows through the light receiving element 1 into a voltage signal and outputs the voltage signal. When the power of the incoming optical signal grows, a distortion might be generated

30

in the output signal of the preamplifier 2 depending on the characteristics of the light receiving element 1 and the characteristics of the preamplifier 2, and therefore the level of a crossing point (or eye crossing) of an eye diagram of the signal input to the data regeneration and clock recovery circuit 4, at which the rising and falling edges of pulses included in the incoming signal cross each other, might be shifted from the DC level (i.e., the mean level of the incoming signal) upwardly or downwardly.

10 In general, the data regeneration and clock recovery circuit 4 receives a differential input, and the AC component of the voltage signal from the capacitor 3 to which a DC bias is applied is input to a normal-phase side of the data regeneration and clock recovery circuit 4 and a threshold voltage used for determining whether the regenerated data is 0 or 1 is supplied to an opposite-phase side of the data regeneration and clock recovery circuit 4. The threshold voltage supplied to the opposite-phase side is equal to the DC bias applied to the normal-phase side.

20 Figs. 13A and 13B are diagrams each showing the waveforms of an incoming optical signal applied to and data regenerated by the data regeneration and clock recovery circuit 4. Fig. 13A shows a case where the input power of the optical signal has a normal level and no distortion is generated in the output signal of the preamplifier 2, and Fig. 13B shows a case where the input power of the optical signal indicates has a large level and a distortion is generated in the output signal of the preamplifier 2.

As shown in Fig. 13A, when no distortion is generated in the output signal of the preamplifier 2 and the output signal

has an excellent waveform, the waveform of the output signal can be symmetric with respect to the DC level and the level of the crossing point of the eye diagram of the output signal at which the rising and falling edges of the waveform cross each other corresponds to the mean level of the waveform. Therefore, since the crossing point thus corresponds to the threshold voltage, when a waveform 101 is input to the data regeneration and clock recovery circuit 4, the data regeneration and clock recovery circuit 4 regenerates data having a waveform 103, and when a waveform 102 is input, the data regeneration and clock recovery circuit 4 regenerates data having a waveform 104. As a result, the rising and falling edges of the regenerated data waveform 103 coincide with the falling and rising edges of the regenerated data waveform 104, respectively, and therefore no time difference  $\Delta t$  occurs between them and no jitter occurs in the regenerated data.

However, as shown in Fig. 13B, when a distortion is generated in the output signal of the preamplifier 2, if the crossing point of the eye diagram is shifted upwardly, the mean level of the waveform is increased and therefore the entire of the waveform is seemed to be lowered with respect to the DC level. The crossing point of the eye diagram might be shift downwardly according to the characteristic of the preamplifier 2 instead of being shifted upwardly as shown in Fig. 13B. In Fig. 13 B in which the crossing point of the eye diagram is shifted upwardly with respect to the threshold voltage, when a waveform 105 is input to the data regeneration and clock recovery circuit 4, the data regeneration and clock recovery circuit 4 regenerates data having a waveform 107, and when a waveform 106 is input, the data regeneration and clock recovery circuit 4 regenerates

data having a waveform 108. As a result, the rising and falling edges of the regenerated data waveform 107 do not coincide with the falling and rising edges of the regenerated data waveform 108, respectively, and therefore a time difference  $\Delta t$  occurs between them and jitter occurs in the regenerated data.

A problem with the prior art optical receiver constructed as mentioned above is that when a distortion occurs in a signal input to the data regeneration and clock recovery circuit 4, and therefore the crossing point of an eye diagram of the input signal at which the rising and falling edges of the input signal cross each other is shifted from the mean level of the input signal, jitter can occur in the regenerated data.

#### SUMMARY OF THE INVENTION

The present invention is proposed to solve the above-mentioned problems, and it is therefore an object of the present invention to provide a DC bias control circuit, an optical receiver, and a DC bias control method capable of reducing the amount of jitter in regenerated data even if a distortion occurs in an input signal and therefore the crossing points where the rising and falling edges of two possible waveforms of the signal cross each other are shifted from the mean level of each of the two possible waveforms.

In accordance with an aspect of the present invention, there is provided a DC bias control circuit for controlling a DC bias added to an AC component of an output signal delivered from an amplifier to a data regeneration circuit that regenerates data from the AC component of the output signal from the amplifier based on a predetermined threshold voltage, wherein the DC bias control circuit controls the DC bias based on a HIGH level, a

DC level, and a LOW level of the signal output from the amplifier.

In accordance with another aspect of the present invention, the DC bias control circuit comprises: a HIGH level detector for detecting a HIGH level of the output signal from the amplifier; a DC level detector for detecting a DC level of the output signal from the amplifier; a LOW level detector for detecting a LOW level of the output signal from the amplifier; a first subtracting circuit for determining a first subtraction result by subtracting the DC level from the HIGH level; a second subtracting circuit for determining a second subtraction result by subtracting the LOW level from the DC level; a third subtracting circuit for determining a third subtraction result by subtracting the second subtraction result from the first subtraction result; and a correction circuit for correcting the DC bias by weighting the third subtraction result according to characteristics of the amplifier, and by determining a difference between a level of a crossing point of an eye diagram of the output signal from the amplifier, at which rising and falling edges of pulses included in the output signal from the amplifier cross each other, and the DC level.

In accordance with a further aspect of the present invention, there is provided an optical receiver comprising: a light receiving element for converting an incoming optical signal into an electrical current signal; a preamplifier for converting the electrical current signal which flows through the light receiving element into a voltage signal; and a data regeneration and clock recovery circuit for applying a DC bias to an AC component of the voltage signal from the preamplifier, and for reshaping and regenerating data and recovering a clock from the AC component based on a predetermined threshold voltage,

wherein the optical receiver controls the DC bias based on a HIGH level, a DC level, and a LOW level of the output signal from the preamplifier.

In accordance with another aspect of the present invention,  
5 the optical receiver further comprises: a HIGH level detector for detecting a HIGH level of the output signal from the preamplifier; a DC level detector for detecting a DC level of the output signal from the preamplifier; a LOW level detector for detecting a LOW level of the output signal from the  
10 preamplifier; a first subtracting circuit for determining a first subtraction result by subtracting the DC level from the HIGH level; a second subtracting circuit for determining a second subtraction result by subtracting the LOW level from the DC level; a third subtracting circuit for determining a third subtraction  
15 result by subtracting the second subtraction result from the first subtraction result; and a correction circuit for correcting the DC bias by weighting the third subtraction result according to characteristics of the light receiving element and characteristics of the amplifier, and by determining a difference  
20 between a level of a crossing point of an eye diagram of the output signal from the preamplifier, at which rising and falling edges of pulses included in the output signal from the preamplifier cross each other, and the DC level.

In accordance with a further aspect of the present  
25 invention, there is provided a method of controlling a DC bias added to an AC component of an output signal delivered from an amplifier to a data regeneration circuit that regenerates data from the AC component of the output signal from the amplifier based on a predetermined threshold voltage, the method comprising  
30 the steps of: detecting a HIGH level of the output signal from

the amplifier; detecting a DC level of the output signal from the amplifier; detecting a LOW level of the output signal from the amplifier; determining a first subtraction result by subtracting the DC level from the HIGH level; determining a second subtraction result by subtracting the LOW level from the DC level; 5 determining a third subtraction result by subtracting the second subtraction result from the first subtraction result; and correcting the DC bias by weighting the third subtraction result according to characteristics of the amplifier, and by determining 10 a difference between a level of a crossing point of an eye diagram of the output signal from the amplifier, at which rising and falling edges of pulses included in the output signal from the amplifier cross each other, and the DC level.

Accordingly, the present invention offers an advantage 15 of being able to reduce the amount of jitter in regenerated data.

Further objects and advantages of the present invention will be apparent from the following description of the preferred embodiments of the invention as illustrated in the accompanying drawings.

20

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the structure of an optical receiver according to a first embodiment of the present invention;

25 Fig. 2 is a circuit diagram showing the structure of a High level detection circuit of the optical receiver according to the first embodiment of the present invention;

Fig. 3 is a circuit diagram showing the structure of a Low level detection circuit of the optical receiver according 30 to the first embodiment of the present invention;

Fig. 4A is a block diagram showing the structure of a circuit including the function of the High level detection circuit and the function of the Low level detection circuit in the optical receiver according to the first embodiment of the present invention;

Fig. 4B is a diagram showing a histogram of sampled values of an analog-to-digital converted output signal of a preamplifier of the optical receiver according to the first embodiment of the present invention;

Fig. 5 is a circuit diagram showing the structure of an example of a DC level detection circuit of the optical receiver according to the first embodiment of the present invention;

Fig. 6 is a circuit diagram showing the structure of another example of the DC level detection circuit of the optical receiver according to the first embodiment of the present invention;

Figs. 7A and 7B are diagrams each showing the waveform of a signal input to a data regeneration and clock recovery circuit of the optical receiver according to the first embodiment of the present invention when an output signal of a preamplifier has a distortion;

Fig. 8 is a diagram showing an example of a weighting correction characteristic of a correction circuit of the optical receiver according to the first embodiment of the present invention;

Fig. 9 is a diagram showing a relationship between the weighting correction characteristic of the correction circuit of the optical receiver according to the first embodiment of the present invention and actual characteristics of a light receiving element and the preamplifier;

Fig. 10 is a diagram showing a relationship between the



weighting correction characteristic of the correction circuit of the optical receiver according to the first embodiment of the present invention and the actual characteristics of the light receiving element and the preamplifier;

5           Fig. 11 is a block diagram showing the structure of a DC bias control circuit according to a second embodiment of the present invention;

Fig. 12 is a block diagram showing the structure of a prior art photoreceiver; and

10           Figs. 13A and 13B are diagrams each showing the waveforms of an input optical signal applied to and data regenerated by a data regeneration and clock recovery circuit of the prior art photoreceiver.

# 15           DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

## Embodiment 1.

Fig. 1 is a block diagram showing the structure of an optical receiver according to a first embodiment of the present invention. In Fig. 1, a light receiving element 1, a preamplifier 2, a capacitor 3, and an data regeneration and clock recovery circuit 4 have the same structures as those of the prior art optical receiver shown in Fig. 12, respectively. The explanation of those components designated by the same reference numerals will be omitted hereafter. Reference numeral 11 denotes a High level detection circuit for detecting a High level of an output signal output from the preamplifier 2, reference numeral 12 denotes a DC level detection circuit for detecting a DC level of the output signal output from the preamplifier 2, and reference numeral 13 denotes a Low level detection circuit for detecting a Low level of the output signal output from the preamplifier

20

25

30

2.

Furthermore, in Fig. 1, reference numeral 14 denotes a subtracting circuit (first subtracting circuit) for determining a first subtraction result by subtracting the DC level of the output signal detected by the DC level detection circuit 12 from the High level of the output signal detected by the High level detection circuit 11, and reference numeral 15 denotes a subtracting circuit (second subtracting circuit) for determining a second subtraction by subtracting the Low level of the output signal detected by the Low level detection circuit 13 from the DC level of the output signal detected by the DC level detection circuit 12.

In addition, in Fig. 1, reference numeral 16 denotes a subtracting circuit (third subtracting circuit) for determining a third subtraction result by subtracting the second subtraction result determined by the subtracting circuit 15 from the first subtraction result determined by the subtracting circuit 14, and reference numeral 17 denotes a correction circuit for weighting the third subtraction result determined by the subtracting circuit 16 according to characteristics of the light receiving element 1 and characteristics of the preamplifier 2, and for determining a difference  $\Delta V$  between the level of a crossing point (or eye crossing) of an eye diagram of the output signal from the preamplifier 2, at which the rising and falling edges of pulses included in the output signal from the preamplifier 2 cross each other, and the DC level, so as to reduce a DC bias applied to a normal-phase side of an input of the data regeneration and clock recovery circuit 4 by only  $\Delta V$ .

Fig. 2 is a circuit diagram showing the structure of the High level detection circuit 11. The High level detection

circuit 11 detects the High level of the output signal of the preamplifier 2 by using a half-wave rectification circuit that consists of a capacitor 21, a resistor 22, a diode 23, and a capacitor 24. Fig. 3 is a circuit diagram showing the structure of the Low level detection circuit 13. The Low level detection circuit 13 detects the Low level of the output signal of the preamplifier 2 by using a half-wave rectification circuit that consists of a capacitor 25, a resistor 26, a diode 27, and a capacitor 28.

Fig. 4A is a block diagram showing the structure of a circuit including the function of the High level detection circuit 11 and the function of the Low level detection circuit 13. In the figure, reference numeral 31 denotes an AD conversion circuit for converting the output signal from the preamplifier 2 into an equivalent digital value, reference numeral 32 denotes a control circuit for sampling the converted digital value at predetermined intervals determined by sampling pulses applied thereto, and for acquiring a histogram of sampled values so as to determine the level of the largest number of accumulations as the High level or Low level of the output signal, and reference numeral 33 denotes a memory for accumulating and storing the sampled values on a level-by-level basis under control of the control circuit 32.

Fig. 5 is a circuit diagram showing the structure of an example of the DC level detection circuit 12. The DC level detection circuit 12 includes two resistors 41 and 42 for voltage-dividing the output signal of the preamplifier 2 having a DC level of  $V_{dc}$ , and an amplifier 43 for blocking high-frequency components of the voltage-divided output signal and for amplifying low-frequency components of the voltage-divided

output signal.

Fig. 6 is a circuit diagram showing the structure of another example of the DC level detection circuit 12. The DC level detection circuit 12 includes a capacitor 44 for blocking DC components of the output signal of the preamplifier 2 and a resistor 45 connected to a power supply having a DC level of Vdc. When using the DC level detection circuit 12 shown in Fig. 6, there is a necessity to use the High level detection circuit 11 shown in Fig. 2 and the Low level detection circuit 13 shown in Fig. 3, they having a common power supply of Vdc.

In operation, the light receiving element 1 and the preamplifier 2 shown in Fig. 1 operate in the same way that those of the prior art photo receiver shown in Fig. 12 do. The High level detection circuit 11 shown in Fig. 2 performs half-wave rectification on the output signal of the preamplifier 2 having a DC level of Vdc, as can be seen from the waveforms of an input and output of the High level detection circuit 11, so as to detect the High level of the output signal of the preamplifier 2.

Similarly, the Low level detection circuit 13 shown in Fig. 3 performs half-wave rectification on the output signal of the preamplifier 2 having a DC level of Vdc, as can be seen from the waveforms of an input and output of the Low level detection circuit 13, so as to detect the Low level of the output signal of the preamplifier 2.

In addition, in the circuit shown in Fig. 4A including the function of the High level detection circuit 11 and the function of the Low level detection circuit 13, the AD conversion circuit 31 converts the output signal from the preamplifier 2 into an equivalent digital value, and the control circuit 32 then samples the converted digital value at predetermined

intervals determined by sampling pulses whose repetition rate is greater than a data transmission rate at which data are transmitted, and accumulates and stores sampled values in the memory 33 on a level-by-level basis. The control circuit 32  
 5 acquires a histogram of the sampled values accumulated on a level-by-level basis, as shown in Fig. 4B, so as to determine the level of the largest number of accumulations as the High level or Low level of the output signal of the preamplifier 2.

The DC level detection circuit 12 detects the DC level  
 10 of the output signal of the preamplifier 2. In the DC level detection circuit 12 shown in Fig. 5, the output signal from the preamplifier 2 having a DC level of  $V_{dc}$  is voltage-divided by the resistors 41 and 42 and is then input to the amplifier 43. Assuming that the resistors 41 and 42 have resistance values  
 15  $R_1$  and  $R_2$ , respectively, the voltage-divided DC level  $V_0$  is given by the following equation (1).

$$V_0 = V_{dc} \times R_2 / (R_1 + R_2) \quad (1)$$

20 The voltage-divided DC level  $V_0$  is then input to the amplifier 43. The amplifier 43 blocks high-frequency components and amplifies low-frequency components, and has a gain  $G$  set to  $(R_1 + R_2) / R_2$ . Therefore, the output of the amplifier 43 has a voltage  $V_1$  given by the following equation (2).

25

$$V_1 = V_0 \times G = V_0 \times (R_1 + R_2) / R_2 \quad (2)$$

Substituting the above-mentioned equation (1) into the above-mentioned equation (2) yields the output voltage  $V_1$  of  
 30 the amplifier 43 given by the following equation (3).

$$\begin{aligned}
 V1 &= V0 \times (R1+R2) / R2 \\
 &= Vdc \times (R2 / (R1+R2)) \times ((R1+R2) / R2) \\
 &= Vdc
 \end{aligned}
 \tag{3}$$

5

In other words, the DC level Vdc of the output signal of the preamplifier 2 is detected.

In the DC level detection circuit 12 shown in Fig. 6, the capacitor 44 blocks the DC level from the preamplifier 2, and a DC level Vdc newly given by a power supply is output from the DC level detection circuit 12 to the subtracting circuits 14 and 15, just as it is. The DC level Vdc from the power supply is equal to the power supply Vdc of the High level detection circuit 11 shown in Fig. 2 and is also equal to the power supply Vdc of the Low level detection circuit 13 shown in Fig. 3.

In Fig. 1, the subtracting circuit 14 subtracts the DC level detected by the DC level detection circuit 12 from the High level detected by the High level detection circuit 1 so as to calculate a voltage difference  $\Delta V_{high}$  between the High level and the DC level, which is the first subtraction result. The subtracting circuit 15 subtracts the Low level detected by the Low level detection circuit 13 from the DC level detected by the DC level detection circuit 12 so as to calculate a voltage difference  $\Delta V_{low}$  between the DC level and the Low level, which is the second subtraction result. The subtracting circuit 16 subtracts  $\Delta V_{low}$  which is the second subtraction result from  $\Delta V_{high}$  which is the first subtraction result so as to calculate  $(\Delta V_{high} - \Delta V_{low})$ , which is the third subtraction result.

The correction circuit 17 weights  $(\Delta V_{high} - \Delta V_{low})$  which is the third subtraction result from the subtracting circuit

30

16 according to input/output characteristics of the light  
 receiving element 1 and input/output characteristics of the  
 preamplifier 2. The correction circuit 17 then determines a  
 difference  $\Delta V$  between the level of the crossing point of an  
 5 eye diagram of the input wave applied to the data regeneration  
 and clock recovery circuit 4, at which the rising and falling  
 edges of pulses included in the input wave cross each other,  
 and the DC level, so as to reduce the DC bias applied to the  
 normal-phase side of the input of the data regeneration and clock  
 10 recovery circuit 4 by only  $\Delta V$ . Thus, the level of the crossing  
 point of the eye diagram, at which the rising and falling edges  
 of pulses included in the input wave applied to the data  
 regeneration and clock recovery circuit 4 cross each other, can  
 be matched with the threshold voltage, or the difference between  
 15 the level of the crossing point and the threshold voltage can  
 be reduced.

Figs. 7A and 7B are diagrams each showing the waveform  
 of the input of the data regeneration and clock recovery circuit  
 4 when the output signal of the preamplifier 2 has a distortion.  
 20 Fig. 7A shows the waveform of the input without correction of  
 the DC bias, and Fig. 7B shows the waveform of the input with  
 correction of the DC bias. When no correction is performed on  
 the DC bias, since there is a difference  $\Delta V$  between the level  
 of the crossing point and the DC level (i.e. threshold voltage),  
 25 as shown in Fig. 7A, jitter occurs in the data output from the  
 data regeneration and clock recovery circuit 4, as in the prior  
 art case of Fig. 13B.

On the other hand, as shown in Fig. 7B, the correction  
 circuit 17 can reduce the DC bias applied to the normal-phase  
 30 side of the input of the data regeneration and clock recovery

circuit 4 by only  $\Delta V$  so as to make the level of the crossing point of the eye diagram of the input wave match with the threshold voltage. Therefore, when a waveform 111 is input to the data regeneration and clock recovery circuit 4, data having a waveform 113 is regenerated by the data regeneration and clock recovery circuit 4. On the other hand, when a waveform 112 is input to the data regeneration and clock recovery circuit 4, data having a waveform 114 is regenerated by the data regeneration and clock recovery circuit 4. As a result, the rising and falling edges of the regenerated data waveform 113 coincide with the falling and rising edges of the regenerated data waveform 114, respectively, and therefore a time difference  $\Delta t$  does not occur between them and no jitter occurs in the regenerated data.

Next, a description will be made as to the weighting which is performed on  $(\Delta V_{\text{high}} - \Delta V_{\text{low}})$  according to the input/output characteristics of the light receiving element 1 and the input/output characteristics of the preamplifier 2. Fig. 8 is a diagram showing an example of a weighting correction characteristic of the correction circuit 17, and shows a relationship between  $(\Delta V_{\text{high}} - \Delta V_{\text{low}})$  and (the level of the crossing point-DC level =  $\Delta V$ ) when the output signal of the preamplifier 2 has a distortion. In Fig. 8, a region in the positive horizontal axis shows a correction characteristic when the output signal of the preamplifier 2 has a distortion and the level of the crossing point of the eye diagram of the input wave is shifted downwardly, i.e., decreased, and another region in the negative horizontal axis shows a correction characteristic when the output signal of the preamplifier 2 has a distortion and the level of the crossing point of the eye diagram of the input wave is shifted upwardly, i.e., increased.



In the correction characteristic shown in Fig. 8, it is assumed that the duration of each 1-bit data is 400psec, the amplitude of the input wave which is equal to the difference between the High level and the Low level is 400mV, and the rise time and fall time of the input wave are always constant and are 80psec. Furthermore, in Fig. 8,  $(\Delta V_{\text{high}} - \Delta V_{\text{low}})$  in the horizontal axis is proportional with (the level of the crossing point - DC level =  $\Delta V$ ) in the vertical axis.  $(\Delta V_{\text{high}} - \Delta V_{\text{low}})$ , which is the third subtraction result from the subtracting circuit 16, is multiplied by a constant value (in this case, -0.75) and the multiplication result is output as  $\Delta V$  from the correction circuit 17. The DC bias is decreased by only  $\Delta V$  so that the level of the crossing point is made to match with the threshold voltage of the data regeneration and clock recovery circuit 4.

Fig. 9 is a diagram showing a relationship between the weighting correction characteristic of the correction circuit 17 and  $(\Delta V_{\text{high}} - \Delta V_{\text{low}})$  - (the level of the crossing point - DC level =  $\Delta V$ ) characteristic of the input wave actually output from the preamplifier 2, which is associated with the characteristics of the light receiving element 1 of the characteristics of the preamplifier 2. In the figure, reference numeral 201 shows a plot representing an example of the characteristic of the input wave actually output from the preamplifier 2, and reference numeral 202 shows a plot representing the weighting correction characteristic of the correction circuit 17 which is the same as that shown in Fig. 8. As shown in Fig. 9, although  $(\Delta V_{\text{high}} - \Delta V_{\text{low}})$  is not proportional with (the level of the crossing point - DC level =  $\Delta V$ ) in the characteristic of the input wave actually output

from the preamplifier 2, the difference between the level of the crossing point and the threshold voltage can be reduced by determining  $\Delta V$  according to the weighting correction characteristic plot 211 that approximate the characteristic of the input wave actually output from the preamplifier 2, and therefore the jitter characteristic of the data regenerated when the output signal from the preamplifier 2 has a distortion can be improved.

Fig. 10 is a diagram showing another example of the relationship between the weighting correction characteristic of the correction circuit 17 and  $(\Delta V_{\text{high}} - \Delta V_{\text{low}}) - (\text{the level of the crossing point} - \text{DC level} = \Delta V)$  characteristic of the input wave actually output from the preamplifier 2, which is associated with the characteristics of the light receiving element 1 of the characteristics of the preamplifier 2. In the figure, reference numeral ~~201~~<sup>202</sup> shows a plot representing an example of the characteristic of the input wave actually output from the preamplifier 2, reference numeral 211 shows a plot representing the weighting correction characteristic of the correction circuit 17 which is the same as that shown in Fig. 8, and reference numeral 212 shows a plot representing another weighting correction characteristic of the correction circuit 17.

As shown in Fig. 10, although  $(\Delta V_{\text{high}} - \Delta V_{\text{low}})$  is not proportional with  $(\text{the level of the crossing point} - \text{DC level} = \Delta V)$  in the characteristic of the input wave actually output from the preamplifier 2, the difference between the level of the crossing point and the threshold voltage can be reduced by determining  $\Delta V$  according to the weighting correction characteristic plots 211 and 212 that approximate the

characteristic of the input wave actually output from the preamplifier<sup>2</sup> (that is, the weighting correction characteristic plot 212 is used in the region in the positive horizontal axis, whereas the other weighting correction characteristics plot 211 is used in the region in the negative horizontal axis) and therefore the jitter characteristic of the data regenerated when the output signal from the preamplifier 2 has a distortion can be improved.

Thus, the best weighting correction characteristic plot is used according to the characteristics of the light receiving element 1 and the characteristics of the preamplifier 2. Furthermore, since  $(\Delta V_{\text{high}} - \Delta V_{\text{low}})$  and (the level of the crossing point - the DC level) change in proportional with the amplitude of the input wave, respectively, even when the amplitude of the input wave changes, the ratio of  $(\Delta V_{\text{high}} - \Delta V_{\text{low}})$  and (the level of the crossing point - the DC level) is kept constant regardless of changes in the amplitude of the input wave. Therefore, the improvement of the jitter characteristics can be obtained regardless of the amplitude of the input wave if weighting correction characteristics as shown in Figs. 8 to 10 are provided, for example, according to the characteristics of the light receiving element 1 and the characteristics of the preamplifier 2.

As mentioned above, in accordance with the first embodiment, the optical receiver detects a HIGH level, a DC level, and a LOW level of an output signal from a preamplifier 2, determines a first subtraction result by subtracting the DC level from the HIGH level, determines a second subtraction result by subtracting the LOW level from the DC level, determines a third subtraction result by subtracting the second subtraction result from the

first subtraction result, and corrects a DC bias by weighting the third subtraction result according to characteristics of a light receiving element 1 and characteristics of the preamplifier 2, so that the level of a crossing point of an eye diagram of the output signal from the preamplifier, at which the rising and falling edges of pluses included in the output signal cross each other, is made to match with or be close to a threshold voltage, even though the input signal has a distortion and the level of the crossing point is shifted from the mean level of the input waveform. Accordingly, the present embodiment offers an advantage of being able to reduce the amount of jitter in regenerated data.

#### Embodiment 2.

In the above-mentioned first embodiment, the optical receiver that regenerates data and recovers a clock from an incoming optical signal is explained. The present invention is also applicable to a DC bias control circuit for use with a data regeneration circuit that receives an electrical signal which is similar to an optical signal and that regenerates data from the electrical signal.

Fig. 11 is a block diagram showing the structure of a DC bias control circuit according to a second embodiment of the present invention. In Fig. 11, reference numeral 2a denotes an amplifier for amplifying a signal applied thereto, reference numeral 4a denotes a data regeneration circuit for regenerating data from an output signal of the amplifier 2a based on a predetermined threshold voltage, and reference numeral 17a denotes a correction circuit for weighting a third subtraction result determined by a subtracting circuit 16 according to

characteristics of the amplifier 2a, and for determining a difference  $\Delta V$  between the level of a crossing point of an eye diagram of the output signal from the amplifier 2a, at which the rising and falling edges of pluses included in the output  
 5 signal cross each other, and a DC level, so as to reduce a DC bias applied to a normal-phase side of an input of the data regeneration circuit 4a by only  $\Delta V$ .

Furthermore, in Fig. 11, reference numeral 18 denotes the DC bias control circuit for controlling the DC bias of the signal  
 10 input to the data regeneration circuit 4a according to the signal output from the amplifier 2a. The DC bias control circuit includes a High level detection circuit 11, a DC level detection circuit 12, a Low level detection circuit 13, a subtracting circuit 14, a subtracting circuit 15, the subtracting circuit  
 15 16, and the correction circuit 17a. The other structure of the DC bias control circuit is the same as that of the photo receiver of the first embodiment shown in Fig. 1, and the explanation of the same components designated by the same reference numerals will be omitted hereafter.

20 In operation, the High level detection circuit 11, the DC level detection circuit 12, and the Low level detection circuit 13 detect the High level, the DC level, and the Low level of the output signal of the amplifier 2a, respectively, like those of the photo receiver of the first embodiment. Furthermore,  
 25 the subtracting circuit 14, the subtracting circuit 15, and the subtracting circuit 16 also determine the first subtraction result, the second subtraction result, and the third subtraction result, respectively, like those of the photo receiver of the first embodiment.

30 The correction circuit 17a weights ( $\Delta V_{\text{high}} - \Delta V_{\text{low}}$ ) which

is the third subtraction result determined by the subtracting circuit 16 according to the input/output characteristics of the amplifier 2a, and then determines the difference  $\Delta V$  between the level of the crossing point of the eye diagram of the output signal from the amplifier 2a, at which the rising and falling edges of pluses included in the output signal cross each other, and the DC level, so as to reduce the DC bias applied to the normal-phase side of the input of the data regeneration circuit 4a by only  $\Delta V$ . Thus, the level of the crossing point of the eye diagram of the output signal from the amplifier 2a, at which the rising and falling edges of pluses included in the output signal cross each other, can be matched with the threshold voltage, or the difference between the level of the crossing point and the threshold voltage can be reduced.

As mentioned above, in accordance with the second embodiment, the DC bias control circuit detects a HIGH level, a DC level, and a LOW level of an output signal from an amplifier 2a, determines a first subtraction result by subtracting the DC level from the HIGH level, determines a second subtraction result by subtracting the LOW level from the DC level, determines a third subtraction result by subtracting the second subtraction result from the first subtraction result, and corrects a DC bias by weighting the third subtraction result according to characteristics of the amplifier 2a, so that the level of a crossing point of an eye diagram of the output signal from the amplifier, at which the rising and falling edges of pluses included in the output signal cross each other, is made to match with or be close to a threshold voltage of a data regeneration circuit 4a, even though the input signal has a distortion and the level of the crossing point is shifted from the mean level

of the input waveform. Accordingly, the present embodiment offers an advantage of being able to reduce the amount of jitter in regenerated data.

Many widely different embodiments of the present invention  
5 may be constructed without departing from the spirit and scope  
of the present invention. It should be understood that the  
present invention is not limited to the specific embodiments  
described in the specification, except as defined in the appended  
claims.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218